

Module | Audio | Video  
 Modules | Audio | Video

Audio | Video-Modulatorkassetten | Single  
 Audio | Video modulator modules | single

- CCD-Überwachungs-kamera, Videokamera, DVD-Player etc. anschließ-bar
- nachbarkanaltauglich
- CCD camera, video camera or VCR etc. can be connected
- adjacent channel compatible

premium-line



Artikel Article	SKM 1-03	SKM 1-04	SKM 1-06
Artikelnummer Part No.	SKM00103	SKM00104	SKM00106
Verpackungseinheit Packing unit		1	
Eingänge Inputs	1	1	1
Video Video			
Signalart Type of signal	FBAS/S-Video/RGB/YPbPr CVBS/S-Video/RGB/YPbPr		VGA/FBAS/RGB/YPbPr VGA/CVBS/RGB/YPbPr
Eingangsspegel typ. Typ. input level		1 Vss	
Eingangsimpedanz Input impedance		75 Ohm nominal	
Frequenzbereich Frequency range		20 Hz...5 MHz	
Anschlüsse Connectors	1 x Cinch Buchse   3 x Cinch Buchse   Mini-DIN-S-Video-Buchse 1 x Cinch female   3 x Cinch female   Mini-DIN female connector		VGA 15 pol. Mini D-Sub Buchse 1 x Cinch Buchse   3 x Cinch Buchse VGA 15 pol. mini D Sub female 1 x Cinch female/3 x Cinch female
Audio Audio			
Eingangsspegel typ. Typ. input level		500mV eff.	
Eingangsimpedanz typ. Typ. input impedance		4,7 kOhm	
Frequenzbereich Frequency range		20 Hz...15 kHz	
Anschlüsse Connectors		2 x Cinchbuchsen 2 x Cinch female	
Monitor-Ausgang Monitor output			
Anschluss Video Connector video		1 x Cinchbuchse 1 x Cinch female	
Anschlüsse Audio Connectors audio		2 x Cinchbuchsen 2 x Cinch female	
Ausgang Output	COFDM (DVB-T)	QAM (DVB-C)	QAM (DVB-C)
Ausgangsspegel Output level		85...105 dBµV	
Ausgangsfrequenzbereich Output frequency range		111...862 MHz	
Ausgangskanäle Output channels		S2...K69 nachbarkanaltauglich (VSB) S2...K69 adjacent channel compatible	
TV-Normen TV standards	DVB-T	DVB-C	DVB-C
Modulation Modulation	IFFT 2k mode, QPSK, QAM16, QAM64	QAM32, QAM64, QAM 128, QAM 256	QAM32, QAM64, QAM 128, QAM 256
Übertragungsmodus Transmission mode	FFT 2 K	-	-
Kodiersätze Coding sets	1/2, 2/3, 3/4, 5/6, 7/8	-	-
Schutzintervall Guard interval	1/32	-	-
Ausgangsimpedanz Output impedance		75 Ohm	
Anschlüsse Connector		1 x F-Stecker Quickfix 1 x F male quickfix	
Allgemein Common			
Stromaufnahme Power consumption		16VDC/0,6A	
Umgebungstemperaturbereich Ambient temperature range		-10°C...+50°C	
Maße ca. Dimensions appr.	36 mm x 218 mm x 129 mm		72 mm x 218 mm x 129 mm